

## FreePBX Phone System 100

## FreePBX

### FEATURE SPECIFICATIONS

#### Basic Features

#### Business Features:

- » Flexible time-based call routing
- » Built in conference bridge/service
- » Fax to email
- » Hunt / Ring groups
- » Music on hold
- » Voicemail blasting
- » Follow me / Find me calling
- » Personal IVRs
- » Wake up calls
- » Support for video calls, IM & presence
- » Secure communications (SRTP/ TLS)
- » Directory & Dictation
- » Calling queues (ACD/IVR)
- » Customizable announcements

#### Calling Features:

- » Three way calling
- » Voicemail
  - > Voicemail to email
- » Caller ID
- » Call transfer
- » Call recording
- » Do not disturb
- » Call forwarding
- » Call waiting
- » Call history
- » Call detail records and call event logging
- » Speed dials
- » Caller blacklisting
- » Paging / Intercom
- » Call screening
- » DISA

#### Telephony Support:

- » Open standards support for multiple signaling protocols
  - > SIP
  - > IAX2
  - > \*PRI/T1/E1
  - > \*POTS/Analog
  - > \*ISDN
- » Soft phone support
- \*Not available on FreePBX 40
- » WebRTC
- » Browser-based calling (thru UCP)
- » Specialty device support
  - > Door phones
  - > Overhead paging
  - > Strobe alerts
  - > Paging & voice gateways
  - > Failover devices

#### Multiple Language Support:

- » English
- » Bulgarian
- » Chinese
- » German
- » Hebrew
- » Hungarian
- » Italian
- » Portuguese
- » Russian
- » Swedish
- » Spanish
- » Japanese

#### End User Applications:

- » User Control Panel (UCP)

#### Administration:

- » Bulk import utilities
- > Trunks
- > Extensions
- > Users
- > Phone numbers
- » System dashboards
- » Integrated intrusion detection

#### Physical Features

##### FreePBX 40:

- » Unit dimensions
  - > 127mm (W) x 127mm (D) x 50mm (H)
- » Unit weight
  - > .68kgs (1.5lbs)
- » External universal AC/DC power brick

##### FreePBX 300:

- » Unit dimensions
  - > 430mm (W) x 305mm (D) x 45mm (H)
- » Unit weight
  - > 4.3kgs (9.5lbs)
- » Internal 100~240V power supply

##### FreePBX 60:

- » Unit dimensions
  - > 430mm (W) x 320mm (D) x 45mm (H)
- » Unit weight
  - > 3.95kgs (8.7lbs)
- » Internal 100~240V power supply

##### FreePBX 1000:

- » Unit dimensions
  - > 430mm (W) x 470mm (D) x 45mm (H)
- » Unit weight
  - > 15kgs (33lbs)
- » Dual modular internal 100~240V power supplies

##### FreePBX 100:

- » Unit dimensions
  - > 430mm (W) x 320mm (D) x 45mm (H)
- » Unit weight
  - > 3.95kgs (8.7lbs)
- » Internal 100~240V power supply



#### Enhanced Features

#### Licensing Options:

- » XactView
  - > Call management and presence desktop for end users
- » Zulu UC (20 Pack)
  - > Desktop integration
- » Call/Contact Center Features
  - > Enhanced call center functionality
- » EndPoint Manager
  - > Third party phone support for non-Sangoma IP phones
- » High Availability
  - > 1:1 active/standby two-box redundancy to guarantee business continuity (Not available on FreePBX 40 & 60)

