

FreePBX Phone System 40

FreePBX

FEATURE SPECIFICATIONS

Basic Features

Business Features:

- » Flexible time-based call routing
- » Built in conference bridge/service
- » Fax to email
- » Hunt / Ring groups
- » Music on hold
- » Voicemail blasting
- » Follow me / Find me calling
- » Personal IVRs
- » Wake up calls
- » Support for video calls, IM & presence
- » Secure communications (SRTP/ TLS)
- » Directory & Dictation
- » Calling queues (ACD/IVR)
- » Customizable announcements

Calling Features:

- » Three way calling
- » Voicemail
 - > Voicemail to email
- » Caller ID
- » Call transfer
- » Call recording
- » Do not disturb
- » Call forwarding
- » Call waiting
- » Call history
 - > Call detail records and call event logging
- » Speed dials
- » Caller blacklisting
- » Paging / Intercom
- » Call screening
- » DISA

Telephony Support:

- » Open standards support for multiple signaling protocols
 - > SIP
 - > IAX2
 - > *PRI/T1/E1
 - > *POTS/Analog
 - > *ISDN
- » Soft phone support
- » WebRTC
 - > Browser-based calling (thru UCP)
- » Specialty device support
 - > Door phones
 - > Overhead paging
 - > Strobe alerts
 - > Paging & voice gateways
 - > Failover devices

*Not available on FreePBX 40

Multiple Language Support:

- » English
- » Bulgarian
- » Chinese
- » German
- » Hebrew
- » Hungarian
- » Italian
- » Portuguese
- » Russian
- » Swedish
- » Spanish
- » Japanese

End User Applications:

- » User Control Panel (UCP)

Administration:

- » Bulk import utilities
 - > Trunks
 - > Extensions
 - > Users
 - > Phone numbers
- » System dashboards
- » Integrated intrusion detection

Physical Features

FreePBX 40:

- » Unit dimensions
 - > 127mm (W) x 127mm (D) x 50mm (H)
- » Unit weight
 - > .68kgs (1.5lbs)
- » External universal AC/DC power brick

FreePBX 60:

- » Unit dimensions
 - > 430mm (W) x 320mm (D) x 45mm (H)
- » Unit weight
 - > 3.95kgs (8.7lbs)
- » Internal 100~240V power supply

FreePBX 100:

- » Unit dimensions
 - > 430mm (W) x 320mm (D) x 45mm (H)
- » Unit weight
 - > 3.95kgs (8.7lbs)
- » Internal 100~240V power supply

FreePBX 300:

- » Unit dimensions
 - > 430mm (W) x 305mm (D) x 45mm (H)
- » Unit weight
 - > 4.3kgs (9.5lbs)
- » Internal 100~240V power supply

FreePBX 1000:

- » Unit dimensions
 - > 430mm (W) x 470mm (D) x 45mm (H)
- » Unit weight
 - > 15kgs (33lbs)
- » Dual modular internal 100~240V power supplies



Enhanced Features

Licensing Options:

- » XactView
 - > Call management and presence desktop for end users
- » Zulu UC (20 Pack)
 - > Desktop integration
- » Call/Contact Center Features
 - > Enhanced call center functionality
- » EndPoint Manager
 - > Third party phone support for non-Sangoma IP phones
- » High Availability
 - > 1:1 active/standby two-box redundancy to guarantee business continuity (Not available on FreePBX 40 & 60)